



**GATOR GRIP THICK MASTIC
CEMENT ROOF PATCH**

MATERIAL SAFETY DATA SHEET

GATOR GRIP THICK MASTIC CEMENT ROOF PATCH MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Gator Grip Thick Mastic Cement Roof Patch

Manufacturer/Final product Composer: Asphatech

Address: #60 King Street, Princes Town, Trinidad, W.I.

Fax: (868) 655-3418 **Technical:** (868) 681-8326 **Land line:** (868) 290-9973

Website: asphatech.com

Material Product Code: GGTMCRP

SECTION 1: MATERIALS IDENTIFICATION & INFORMATION

COMPONENTS — Chemical name / common name (Hazardous components 1% or greater, carcinogens 1% Or greater)	%	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED
Special blended Asphalt Base	<65%	5mg/M3	5mg/ M3	Ceiling of 10mg / M3
Petroleum White Miner Spirits	<22%	100 ppm	350mg / M3	Max. 3hr. 1,800mg / M3
Cellulose fibers / asbestos free	<7%	As dust	10mg / M3	
Plastic Solution / Powder	<6%	As dust	10mg / M3	

SECTION 2: PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling Point	313 degrees Farenheight	Specific gravity (H2O =1)	>1.0
Vapor pressure (mm Hg and. Temperature)	ND	Melting Point	ND
Vapor Density (Air =1)	ND	Evaporation rate (butyl acetate=1)	ND
Solubility in water	insoluble	Water reactive	None
Appearance and odor: Dark color, vicious liquid, petroleum odor when stirred.			

SECTION 3: FIRE & EXPLOSION HAZARD DATA

Flash Point >100°F. Method used : NFPA	Auto ignition temperature: > 400F	Flammability limits in air % by volume	LEL: 0.9%	UEL: 6.0%
Extinguisher Media: Dry Chemical, Foam.				
Special fire-fighting procedures : N / A				
Unusual fire and explosion hazards: petroleum-based compounds can float in water.				

WHMIS CLASSIFICATION

Class B, Division 2 Flammable Liquids

Class D, Division 2b, Materials Causing other toxic effects

TDG CLASSIFICATION

Tars, Liquid, Class 3, UN 1999 Packing Group 111

GATOR GRIP THICK MASTIC CEMENT ROOF PATCH MATERIAL SAFETY DATA SHEET

SECTION 4: REACTIVITY HAZARD DATA

Stability: stable <input checked="" type="checkbox"/> unstable	Condition to avoid: keep away from heat, sparks, open flame
Incompatibility (materials to avoid) acids, caustics oxidizers.	
Hazardous decomposition products: nitrogen oxides, carbon oxides.	
Hazardous polymerization --- may occur <input checked="" type="checkbox"/> will not occur	Conditions to avoid: N IA

SECTION 5: HEALTH HAZARD DATA

Primary Routes of entry <input checked="" type="checkbox"/> Inhalation: vapors <input checked="" type="checkbox"/> Skin absorption: very slight <input checked="" type="checkbox"/> Ingestion: Slight. Not hazardous:	Carcinogen listed in NTP IARC OSHA <input checked="" type="checkbox"/> Not listed
Health hazard: ACUTE: itching, unconsciousness, dizzy, dry skin, nausea. CHRONIC: difficult breathing (cancer studies inconclusive)	
Signs of systems and exposure: Repeated / continuous exposure can cause chemical pneumonia, liver / kidney damage.	
Medical conditions generally aggravated by exposure: repeated/continuous exposure can aggravate emphysema	
EMERGENCY FIRST AID PROCEDURES: large amounts may need immediate emergency treatment.	
Eye contact: flush eyes for 15 minutes with clean water, GET MEDICAL ATTENTION.	
Skin contact: wash with soap and water; get medical care if irritation persists.	
Inhalation: get to fresh air, administer oxygen or artificial respiration	
Ingestion: DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION QUICKLY.	

GATOR GRIP THICK MASTIC CEMENT ROOF PATCH MATERIAL SAFETY DATA SHEET

SECTION 6: CONTROL & PROTECTIVE MEASURES

Respiratory protection (specify type): organic vapor cartridge if in an enclosed area.		
Protective gloves: impervious to solvents		Eye protection: chemical goggles for vapors optional, none normally needed
Ventilation to be used:	X local exhaust: if outside	X mechanical (general): if inside
	_____ Special	X other (specify): avoid vapor concentration
Other protective clothing and equipment: long sleeve shirt and long pants preferred, none required		
Hygienic work practices: wear gloves to prevent irritations. Wash skin with soap and water or waterless cleaner- con't		
DO NOT WASH SKIN WITH SOLVENTS		

SECTION 7: PRECAUTIONS FOR SAFE HANDLING & USE/LEAK PROCEDURES

Steps to be taken if material is spilled or released: use non-sparking tools with absorbent material (limestone), shovel up and place in closed container for proper disposal.
Waste disposal methods: RCRA regulated material. Consult local, state and federal regulations for permitted land fill disposal of incineration methods.
Precaution to be taken in handling and storing: use in well-ventilated area, store in dry, cool area.
Other precautions and/or special hazards: DO NOT HEAT FOR APPLICATION. Wash contaminated clothing.

MSDS CODE — GGTMRP (Gator Grip Thick Mastic Cement Roof Patch)